

P524 Sealing vapor barrier film



Liner: White siliconized paper 2 sides

Adhesive: Acrylic

Scrim: Polyester

Carrier: Black Polyethylene film

Dimensions

- 25m x 60mm
- Roll : various lengths and widths adapted according to needs

Uses

- Vapor barrier seam tape
- Straight and curved strips for open joint cladding vapor barrier and roofing membrane
- Perform seal and junction between wood panels (eg OSB), vapor barrier and roofing barrier used in the construction and renovation, Passive,...
- Interior and exterior use

Benefits

- Very strong adhesion to wood panel, vapor barrier and roofing barrier
- Very good UV resistance
- Excellent resistance to ageing
- Adhesion on wet surface
- Flexible and conformable
- Hand tearable
- Temperature application : from -10 ° c

Storage and shelf life

- Store the product between 15 and 30°C and 50 ± 15 % RH in the original packaging
- To be used within 6 months after delivery

Properties

Characteristics	Value	Unit. typical value	Test standard
Thickness (without liner)	245*	µm	AFERA 5006
Peel adhesion on steel	≥ 10	N/cm	AFERA 5001
Peel adhesion on membrane**	> 25	N/50mm	NF EN 12316-2
Shear strength on membrane**	> 90	N/50mm	NF EN 12317-2
(*) Typical value			

(**) Product meets CSTB GS20 specifications. Tests performed on main market barrier films

Please note that tests are conducted under standardized conditions and, as a consequence, the results obtained for a specific application may differ from the results presented here above.

ADHEX TECHNOLOGIES only guarantees the conformity of its products with the specifications shown on the technical datasheet, at the time of their delivery.

ADHEX TECHNOLOGIES offers no other guarantee and, in particular, does not guarantee the performance of the product or its safety when used in combination with other materials. ADHEX TECHNOLOGIES does not guarantee products in respect of a particular usage, nor does it guarantee their compatibility with or appropriateness for any industrial application or processing method whatsoever.

Customers are advised to refer to the "General Conditions of Sales and Warranty" which can be found on www.adhex.com

Reference : FT-IND-00133-02

Creation date : 2022/10/17