

RIF. COD.

1	B000028A12	43	B000026A11
2	C440101A01	44	B000021C01
3	C440103A01	45	C742948A01
4	B000028C04	46	C742720A01
5	C450180A01	47	C742736A01
6	D440123A01	48	C450180A01
7	C240160A01	49	C742701A03
8	B000020A06	50	C450180A01
9	C440181A01	51	B000028B12
10	B000020A43	52	D742973A02
11	D440202A01	53	B000022A02
12	B000020A40	54	B000028E12
13	B000020A39	55	B000028C04
14	D440204A01	56	B000028B13
15	B000020A44	57	C742681A01
16	B000023B04	58	C230661A01
17	B000020A52	59	D742640A01
18	C442220A01	60	B000021C01
19	C442225A01	61	C742540A01
20	B000020A60	62	B000028A08
21	D442241A02	63	C742912A07
22	B000020A40	64	B000020B02
23	C642244A01	65	C742937A07
24	B000020B02	66	C742714A01
25	B000020B01	67	B000026A23
26	B000020A02	68	C742710A01
27	D450304A01	69	C742727A01
28	B000020B11	70	B000028B45
29	B000020A02	71	B000022A02
30	D730361A01	72	C742710A01
31	B000020A19	73	C430401A02
32	B000020A19	74	C742949A01
33	B000026A12	75	C742710A03
34	D750411A02	76	B000028A03
35	C450262A01	77	C620820A01
36	B000020A42	78	C620824A01
37	D450283A01	79	C650842A01
38	C442261A02	80	C620884A01
39	B000026A05	81	C742860A01
40	D442484A01	82	D440123A01
41	C742500A01	83	D440202A01
42	D742441A01	84	D440204A01

Codice A742000A07
Modello M42
Tipo Punto SK
Lungh. min. 40 mm.
Lungh. max. 60 mm.

Kode A742000A07
Modell M42
Klammer Typ SK
Min. Länge 40 mm.
Max. Länge 60 mm.

Code A742000A07
Modell M42
Staple type SK
Min. length 40 mm.
Max. length 60 mm.

Code A742000A07
Modèle M42
Agrafe type SK
Longueur min. 40 mm.
Longueur max. 60 mm.

Código A742000A07
Modelo M42
Grapa tipo SK
Largueza min. 40 mm.
Largueza max. 60 mm.

Codigo A742000A07
Modelo M42
Tipo de agrafe SK
Largura min. 40 mm.
Largura max. 60 mm.

DATI TECNICI

Peso: 2370 gr.
Dimensioni: 80-270-346 mm.
Consumo aria: 1,30 NI/colpo (6 bar)
Pressione min.: 4,0 bar
Pressione max.: 7,0 bar

TECHNISCHE DATEN

Gewicht: 2370 gr.
Abmessungen: 80-270-346 mm.
Luftverbrauch: 1,30 NI/pro Schlag (6 bar)
Min.Betriebsdruck: 4,0 bar
Max.Betriebsdruck: 7,0 bar

TECHNICAL FEATURES

Weight: 2370 gr.
Dimensions: 80-270-346 mm.
Air consumption: 1,30 NI/shot (6 bar)
Min.working pressure: 4,0 bar
Max.working pressure: 7,0 bar

DONNEES TECHNIQUES

Poids: 2370 gr.
Dimensions: 80-270-346 mm.
Consommation d'air: 1,30 NI/coup (6 bar)
Pression de fonction min.: 4,0 bar
Pression de fonction max.: 7,0 bar

DATOS TECNICOS

Peso: 2370 gr.
Dimensiones: 80-270-346 mm.
Consumo de aire: 1,30 NI/disparo (6 bar)
Presion min.: 4,0 bar
Presion max.: 7,0 bar

CARACTERISTICAS TECNICAS

Peso: 2370 gr.
Dimensões: 80-270-346 mm.
Consumo de ar: 1,30 NI/disparo (6 bar)
Pressão min.: 4,0 bar
Pressão max.: 7,0 bar

POTENZA ACUSTICA

DIRETTIVA 89/392 CEE
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= 89,2 (dB)
LpA 60S 1M= 88,4 (dB)

SCHALLEISTUNG

EWG RICHTLINIE 89/392
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= 89,2 (dB)
LpA 60S 1M= 88,4 (dB)

NOISE POWER

EEC DIRECTIVE 89/392
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= 89,2 (dB)
LpA 60S 1M= 88,4 (dB)

PUISSANCE ACOUSTIQUE

DIRECTIVE CEE 89/392
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= 89,2 (dB)
LpA 60S 1M= 88,4 (dB)

POTENCIA ACUSTICA

NORMATIVA 89/392 CEE
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= 89,2 (dB)
LpA 60S 1M= 88,4 (dB)

POTENCIA ACUSTICA

DIRETTIVA 89/392 CEE
prEN 12549 (1999)
UNI EN ISO 3744 (1997)
LwA= 89,2 (dB)
LpA 60S 1M= 88,4 (dB)

VIBRAZIONI PRODOTTE

DIRETTIVA 89/392 CEE
ISO/FDIS 8662-11 (1999)
ah.w.3s= 2,7 (m/s²)

GERAETE BEZOGENER

VIBRATIONSWERT
EWG RICHTLINIE 89/392
ISO/FDIS 8662-11 (1999)
ah.w.3s= 2,7 (m/s²)

TOOL RELATED VIBRATION

VALUE
EEC DIRECTIVE 89/392
ISO/FDIS 8662-11 (1999)
ah.w.3s= 2,7 (m/s²)

VALEUR DES VIBRATIONS

PAR LA MACHINE
DIRECTIVE CEE 89/392
ISO/FDIS 8662-11 (1999)
ah.w.3s= 2,7 (m/s²)

VIBRACION PRODUCIDA

NORMATIVA 89/392 CEE
ISO/FDIS 8662-11 (1999)
ah.w.3s= 2,7 (m/s²)

NIVEL DE VIBRACAO

DO PRODUTO
DIRETTIVA 89/392 CEE
ISO/FDIS 8662-11 (1999)
ah.w.3s= 2,7 (m/s²)

B640040A01 O-Ring Kit

742/0 A07/01 08/01

Serial Nr. 80600985

0720

390612